

अनिवार्य आवश्यकतायें  
संख्या: TEC12671906

Essential Requirement  
ER No.: TEC12671906

---

---

Cordless Telephone

© टीईसी, २०१८  
© TEC, 2018

---

---

Issued under MTCTE by:

दूरसंचार अभियांत्रिकी केंद्र  
भारत सरकार  
खुरशीदलाल भवन, जनपथ, नई दिल्ली - 110001, भारत

Telecom Engineering Centre  
Government of India  
Khurshidlal Bhawan, Janpath, New Delhi-110001, INDIA

---



## Essential Requirements for:

# Cordless Telephone

Certification Scheme: **GCS**

Product Fee Group: **A**

This ER covers all types of Cordless Telephones

This product has the following variants:

- 1 Cordless Telephone

## Variant 1 : Cordless Telephone

### Mandatory Parameters

Parameter Name	Standard Name
IT Equipment Safety	IS 13252. IEC:60950-1 or IEC 62368 Annex-A1
Conducted And Radiated Emission - Class B	TEC EMI EMC Standard, CISPR 22/32, EN55022/32. Annex-B
Immunity to Electrostatic Discharge	TEC EMI EMC Standard, EN/IEC:61000-4-2. Annex-B
Immunity to Radiated RF	TEC EMI EMC Standard, EN/IEC:61000-4-3. Annex-B
Immunity to Fast Transients (Burst)	TEC EMI EMC Standard, EN/IEC:61000-4-4. Annex-B
Immunity to Surges	TEC EMI EMC Standard, EN/IEC:61000-4-5. Annex-B
Immunity to RF Field Induced Conducted Disturbance	TEC EMI EMC Standard, EN/IEC:61000-4-6. Annex-B
Immunity to AC Voltage Dips and Short Interruptions	TEC EMI EMC Standard, EN/IEC:61000-4-11. Annex-B
Immunity to DC Voltage Dips and Short Interruptions	EN/IEC:61000-4-29. Annex-B
Acoustic Shock Absorption	P.360. Annex-D
Over Voltage Current Protection on 2W	K.21. Annex-D
EIRP for Cordless Telephone	WPC GSR. Annex-D2
Frequency Band For Cordless Telephone	WPC GSR. Annex-D2
Spurious Emissions for Cordless Phone	Annex-D2
Transmit Power for Cordless Telephone	Annex-D2

### Mandatory Parameters if interface selected: 2 Wire

Parameter Name	Standard Name
Idle State Current for 2 wire Int	ETSI EN 300 001, ETSI TBR-21 Cl. 4.4.1. Annex-D
Insulation Test for 2 wire Int	ETSI EN 300 001. Annex-D
Longitudinal Conversion Loss for 2W Int	Q.552 Cl. 2.2.2. Annex-D
Maximum Loop Current for 2W Int	ETSI EN 300 001, ETSI TBR-21 Cl.4.4.3. Annex-D

